

## Description

The **PS115** power supply provides 10 Amps of current for fixed and P/T/Z cameras. Power is provided to the CX452 card cage in the UTPLinks system for insertion and distribution of power and P/T/Z data. The number of fixed and/or P/T/Z cameras that can be powered by the PS115 is dependent upon the current requirements of the equipment being powered. The PS115 can be located at a mid-span position; i.e. IDF closet or at the “head-end”. These power supplies must be located in close proximity to the CX452.

## Features

- Power is provided to cameras and P/T/Z units in a closed, self-contained system
- PS115 units mount in a 19” rack
- Easy to install and configure
- Designed to be compatible with “Structured Cabling” standards
- Video, data and power can be run in the same Category 5 cable without interference



## Specifications

Size	1.75” H x 19.0” W x 8.6” D
Power Requirements	120 VAC
Output Voltage	28 VAC
Output Current	10 Amps
Enclosure Type	Standard 19” rack, 1 RU in height
Shipping Weight	21lbs



# NITEK®

USA

5410 Newport Drive, # 24  
Rolling Meadows, IL 60008  
Phone: (847) 259-8900  
Fax: (847) 259-1300  
E-mail: [info@nitek.net](mailto:info@nitek.net)  
[WWW.NITEK.NET](http://WWW.NITEK.NET)

EUROPE

De Schans 19-21 2a  
8231 KA Lelystad  
Tel: +31(0)320-2300005  
Fax: +31(0)320-282186  
E-mail: [info@nitek.nl](mailto:info@nitek.nl)  
[WWW.NITEK.NL](http://WWW.NITEK.NL)