



1/2" 1.4/3.5mm C		1/3"	
Focal Length		f=3.5mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Element		6 Group 7 Elements	
Picture Size		4.8x6.4mm	3.6x4.8
Angle	Ver.	76.6°	57.7°
	Hol.	103.6°	77.0°
	Dia.	132.1°	97.5°
Distortion (TV)		-28.0%	
Shooting Range at M. O. D.	Ver.	247mm	
	Hol.	396mm	
	Dia.	688mm	
Minimum Object Distance		0.2m	
Flange Back		17.526 mm in air	
Back Focus		8.89mm in air	
Filter Screw Size			
Front/Rear Effective Dia.		Front: $\phi 19.6$ mm Rear: $\phi 10.4$ mm	
Mount		C-MOUNT	
Exit Pupil		-71.4mm	
Temperature Range		-10~+45° C	
Strong Temperature Range		-40~+60° C	
Resolution		Center:100Line/mm Corner: 40Line/mm	
Stopper Strength		10kgf · cm	
Endurance Tests		Iris:5,000Times Focus:5,000Times	
Operating Torque		Iris:50~600gf · cm Focus:100~1000gf · cm	
Weight		56g±5g	



LM4NCR