

## AXIS Washer Kit B

For clear vision all year round

AXIS Washer Kit B sprays cleaning fluid on the front window of compatible Axis positioning cameras. The kit contains a 23-liter (6-gallon) tank, a pump for delivering cleaning fluid to up to 11 m (36 ft), a hose, a nozzle and a nozzle support bracket.

- > **Sprays cleaning fluid**
- > **Delivers cleaning fluid to up to 11 m (36 ft)**
- > **23-liter tank capacity (6 gallons)**
- > **Compatible with selected Axis positioning cameras**



## AXIS Washer Kit B

General	
<b>Supported products</b>	AXIS T99A10 Positioning Unit 24 V AC/DC AXIS Q8685-E/-LE PTZ Network Cameras AXIS Q87 Series
<b>Casing</b>	Tank: polyethylene Cage: stainless steel Electronics enclosure: technopolymer Nozzle support bracket: stainless steel
<b>Dimensions</b>	301 x 410 x 348 mm (11.8 x 16.1 x 13.7 in)
<b>Weight</b>	6.7 kg (14.8 lb)
<b>Power</b>	230 V AC, 0.5 A, 50/60 Hz 120 V AC, 1 A, 50/60 Hz 24 V AC, 1.8 A, 50/60 Hz
<b>Tank capacity</b>	23 l (6 gal)
<b>Delivery head</b>	Plastic hose with stainless steel nozzle
<b>Tube length</b>	11 m (36 ft)
<b>Elevation</b>	11 m (36 ft), 1 m/sec
<b>Operating conditions</b>	Antifreeze liquid in solution, full performance: -10 °C to 60 °C (14 °F to 140 °F)
<b>Storage conditions</b>	Antifreeze liquid in solution, reduced performance due to higher fluid viscosity at lower temperatures: -25 °C to 60 °C (-13 °F to 140 °F)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	EMC EN 50130-4, EN 61000-6-3, EN 55032 Class B, FCC Part 15 Subpart B Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, VCCI Class B, EAC Safety EN 60950-1, EN 60950-22 Environment IEC/EN 60529 IP56
<b>Included accessories</b>	Installation Guide
<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)